

MEET GEN 5

DAY
NIGHT
THERMAL

2024



THE FUTURE
OF OPTICS

www.atncorp.com

X-Sight 5 / 5 LRF Series ULTRA HD 4K+ SMART DAY & NIGHT VISION RIFLE SCOPE	page 4
X-Sight LTV Series ULTRA LIGHTWEIGHT DAY & NIGHT VISION RIFLE SCOPE	page 6
ThOR 5 / 5 LRF Series SMART HD THERMAL RIFLE SCOPE	page 8
ThOR 5 XD / 5 XD LRF Series 1280X1024 SMART HD THERMAL RIFLE SCOPE	page 10
ThOR LTV Series ULTRA LIGHT THERMAL RIFLE SCOPE	page 12
TICO LTV Series THERMAL CLIP-ON	page 14
ODIN LT Series COMPACT THERMAL MONOCULAR	page 16
BinoX 5 5-20x ULTRA HD 4K+ DAY/NIGHT VISION BINOCULARS W/ LASER RANGEFINDER	page 18
10-42x LRF Series LASER RANGEFINDING BINOCULAR	page 20
BinoX 4T Series SMART HD THERMAL BINOCULARS	page 22
X-Spotter 5 5-20x ULTRA HD 4K+ DAY/NIGHT SPOTTING SCOPE	page 24
NVM14 Series NIGHT VISION MULTI-PURPOSE SYSTEM	page 26
PVS14 Series NIGHT VISION MULTI-PURPOSE SYSTEM	page 27
NVG7 Series NIGHT VISION GOGGLES	page 28
PVS7 Series NIGHT VISION GOGGLES	page 29
PS31 Series NIGHT VISION GOGGLES	page 30
IR850 Pro LONG RANGE INFRA-RED ILLUMINATOR	page 31
IR850 Supernova EXTREME RANGE INFRA-RED ILLUMINATOR	page 31
IR940 LONG RANGE INFRA-RED ILLUMINATOR	page 31
Power Weapon Kit 20,000 mAh BATTERY PACK	page 31
Extended Life Battery Kit 10,000 mAh BATTERY PACK	page 31
X-TRAC 5 TACTICAL REMOTE ACCESS CONTROL SYSTEM	page 31
Tactical Carry Case	page 31
Deluxe Binoculars Bag	page 31
Low profile Quick Detach Heavy Duty Mount	page 32
High profile Quick Detach Heavy Duty Mount	page 32
Quick Detach Mount	page 32
Thermal coyote/boar Target Kit	page 32
Thermal Targets	page 32
X-Sound HEARING PROTECTOR	page 32





ULTRA HD OPTICS

Experience ATN's Ultra HD Optics like never before! Our new 4K "True Color" Sensor is capable of capturing crisp clear images

at the furthest ranges with increased daytime color resolution (4 million colors). With 24,000 shades of grey, you'll also get incredibly smooth nighttime gradations from darkness to light.

All 5th Gen Optics have been redesigned to meet strict specifications to match our 4K sensor performance. The new Quad Core Processor that drives our core allows for faster response, higher

FPS rate, better streaming, and the use of a multitude of new image processing techniques.

The next several pages will help familiarize you with just some of the amazing features the new Smart HD and Ultra HD Optics have to offer.

THE FUTURE OF OPTICS IS HERE!





4K+
SENSOR

SMART HD
OPTICS

5
GEN

X-SIGHT 5 / 5 LRF SERIES

ULTRA HD 4K+ SMART DAY & NIGHT VISION RIFLE SCOPE



*scope view

4K ULTRA HD 4K SENSOR

Experience true-to-life visuals day and night with the new superior 4K sensor.

BUILT-IN LASER RANGEFINDER (OPTIONAL)

Achieve precise shooting and never miss a target with this advanced feature.

ADVANCED BALLISTIC CALCULATOR

Seamlessly integrate shot accuracy by accounting for environmental variables directly within the scope.

4K VIDEO RECORDING

Record and share your experiences in real 4K quality with friends and family.

240 SLOW MOTION

Capture crucial moments with stunning clarity at 240 frames per second.

CUSTOM RETICLE EDITOR

Unleash creativity with ATN to design and share unique reticles.



SPECIFICATIONS

Item	X-Sight 5 3-15x	X-Sight 5 5-25x	X-Sight 5 LRF 3-15x	X-Sight 5 LRF 5-25x
Laser Rangefinder	No		Yes	
Sensor	ATN 4K+ 4056x3040 30/60/120 FPS			
Magnification	3-15x	5-25x	3-15x	5-25x
Field of view	9°	6.3°	9°	6.3°
Field of view	15.7 m / 100 m	11 m / 100 m	15.7 m / 100 m	11 m / 100 m
Core	ATN Gen V Quad Core			
Micro Display	1280x960			
Eye relief	90 mm			
Video Record Resolution	Up to 4K UHD 30/60/120 fps			
Ballistic Calculator	Yes			
WiFi (Streaming, Gallery, & Controls)	iOS, Android			
3D Gyroscope	Yes			
3D Accelerometer	Yes			
RAV (Recoil Activated Video)	Yes			
Electronic Compass	Yes			
Smooth Zoom	Yes			
Radar	Yes			
Reticles	Multiple Patterns & Color Options, User Custom reticles			
Reticle Editor	Yes			
Microphone	Yes			
MicroSD card	4 to 64 Gb (V30 class)			
USB, type C	Yes			
Mount	30 mm Standard Rings (included)			
Battery life (Li-ion)	Up to 14 hours			
Waterproof rating / IP rating	Weather resistant			
Operating Temperature	-20°F to +120°F / -28°C to 48°C			
Dimensions	13.3"x2.2"x2.1" 337x56x54 mm	14.2"x2.2"x2.1" 360x56x54 mm	14.3"x3"x2.2" 362x76x56 mm	15.2"x3"x2.2" 385x76x56 mm
Weight	1.87 lb / 0.85 kg	1.87 lb / 0.85 kg	2.1 lb / 0.95 kg	2.1 lb / 0.95 kg
Warranty	2 years			

*Specifications subject to change without notice.

OPTIONAL ACCESSORIES



**ATN X-TRAC 5
REMOTE CONTROL**



**ATN IR 850 SUPERNOVA
IR ILLUMINATOR**



**ATN WEAPON
BATTERY PACK**




**ATN LP QUICK
DETACH MOUNT**





X-SIGHT LTV SERIES

ULTRA LIGHTWEIGHT DAY & NIGHT VISION RIFLE SCOPE



*scope view

QHD+ SENSOR

Experience crisp, vivid imagery around the clock with ATN. This technology ensures exceptional clarity both day and night.

ERGONOMIC DESIGN AND USER INTERFACE

Features a classic, user-friendly design with a wide field of view, easily mountable on any platform using 30 mm standard mount rings.

ENHANCED NIGHT VISION MODE

Overcome the challenges of darkness with this feature, ensuring uninterrupted performance.

ONE SHOT ZERO

Enables fast and easy sight-in of your scope, along with a selection of multiple reticles.

HD VIDEO RECORDING

Capture your hunting experiences in sharp 720P quality for future enjoyment.

5-15x



3-9x

SPECIFICATIONS


	X-Sight LTV 3-9x	X-Sight LTV 5-15x
Item #	DGWSXS309LTV	DGWSXS515LTV
Magnification	3-9x	5-15x
Sensor	ATN QHD+ M584 Sensor	
Sensor Resolution	2688 x1944 @ 60 fps	
Core	ATN Obsidian LT Core	
Micro Display	1280x720 px	
Eye relief	90 mm	
3D Gyroscope	Yes	
3D Accelerometer	Yes	
Night Vision Mode	Yes	
Video Record	Yes	
Reticles	Multiple Patterns	
Video Record Resolution	1280x720	
Miscro SD Card	4 Gb to 64 Gb	
USB, type C	Charging Port	
Mount	30 mm Standard Rings (included)	
IR Illuminator	Included	
Battery life (Li-ion)	≈ 10 hrs	
Battery type	Internal Lithium Ion Battery	
Waterproof rating / IP rating	Weather resistant	
Dimensions (body only)	12.2"x2.2"x2.2" / 310x55x55 mm	13"x2.2"x2.2" / 330x55x55 mm
Weight	1.6 lb / 745 g	1.7 lb / 780 g
Warranty	2 years	

*Specifications subject to change without notice.

OPTIONAL ACCESSORIES




ATN X-SOUND



ATN IR 850 PRO
IR ILLUMINATOR



ATN WEAPON
BATTERY PACK




ATN QUICK DETACH
MOUNT





THOR 5 / 5 LRF SERIES

SMART HD THERMAL RIFLE SCOPE



*scope view

NEXT GEN ULTRA SENSITIVE THERMAL SENSOR

Delivers richer colors and greater detail, enhancing target detection day or night.

BUILT-IN LASER RANGEFINDER (OPTIONAL)

Enables precise target ranging and accurate shooting over any distance.

ADVANCED BALLISTIC CALCULATOR

Provides precise shot data for your scope, ensuring accuracy and effectiveness.

CUSTOM RETICLE EDITOR

Design and share personalized reticles for a unique hunting experience.

HD VIDEO RECORDING

Capture your hunting adventures in high-definition, reliving each moment with crystal-clear video quality.

ADDITIONAL FEATURES FOR ENHANCED HUNTING

Includes One Shot Zero, Profile Manager, Recoil Activated Video (RAV), and extended battery life, making it an ideal scope for hunters.



SPECIFICATIONS

Model	ThOR 5 320			ThOR 5 LRF 320			ThOR 5 640				ThOR 5 LRF 640				
	ThOR 5 320 3-12x	ThOR 5 320 4-16x	ThOR 5 320 5-20x	ThOR 5 LRF 320 3-12x	ThOR 5 LRF 320 4-16x	ThOR 5 LRF 320 5-20x	ThOR 5 640 2-16x	ThOR 5 640 3-24x	ThOR 5 640 4-32x	ThOR 5 640 5-40x	ThOR 5 LRF 640 2-16x	ThOR 5 LRF 640 3-24x	ThOR 5 LRF 640 4-32x	ThOR 5 LRF 640 5-40x	
Item #	TIWST5319A	TIWST5325A	TIWST5335A	TIWST5319LRF	TIWST5325LRF	TIWST5335LRF	TIWST5625A	TIWST5635A	TIWST5650A	TIWST5675A	TIWST5625LRF	TIWST5635LRF	TIWST5650LRF	TIWST5675LRF	
Laser Rangefinder	No			Yes			No				Yes				
Sensor	320x240 60 fps 12 µm						640x480 60 fps 12 µm								
Magnification	3-12x	4-16x	5-20x	3-12x	4-16x	5-20x	2-16x	3-24x	4-32x	5-40x	2-16x	3-24x	4-32x	5-40x	
Field of view, degrees	11.6x8.7	8.8x6.6	6.3x4.7	11.6x8.7	8.8x6.6	6.3x4.7	17.6x13.2	12.6x9.4	8.8x6.6	5.9x4.4	17.6x13.2	12.6x9.4	8.8x6.6	5.9x4.4	
Core	ATN Gen V Quad Core T														
Micro Display	OLED display 1024x768														
Eye relief	90 mm														
Video Record Resolution	Up to 1280x960 @ 60 fps														
Ballistic Calculator	Yes														
WiFi (Streaming, Gallery, & Controls)	iOS & Android														
Bluetooth	Yes														
3D Gyroscope	Yes														
3D Accelerometer	Yes														
RAV (Recoil Activated Video)	Yes														
Electronic Compass	Yes														
Smooth Zoom	Yes														
Radar	Yes														
Reticles	Multiple Patterns & Color Options, User Custom reticles														
Reticle Editor	Yes														
Microphone	Yes														
MicroSD card	4 to 64 Gb														
USB, type C	Yes														
Mount	30 mm Standard Rings (included)														
Battery life (Li-ion)	10 hrs														
Waterproof rating / IP rating	Weather resistant														
Human Detection Range	750	960	1400	750	960	1400	1250	1600	2150	3300	1250	1600	2150	3300	
Human Recognition Range	335	432	630	335	432	630	560	720	960	1485	560	720	960	1485	
Human Identification Range	205	260	378	205	260	378	330	432	570	680	330	432	570	680	
Operating Temperature	-20°F to +120°F / -28°C to 48°C														
Dimensions	12.4"x2.2"x2.1" 316x56x54 mm			13.4"x3"x2.2" 341x76x56 mm			12.4"x2.2"x2.1" 316x56x54 mm				13"x2.2"x2.1" 330x56x54 mm		13.4"x3"x2.2" 341x75x56 mm		14"x3"x2.2" 355x76x56 mm
Weight	1.93 lb / 0.88 kg			2.1 lb / 0.93 kg			1.93 lb / 0.88 kg				2.5 lb / 1.133 kg		2.1 lb / 0.93 kg		2.7 lb / 1.203 kg
Warranty	3 years														

*Specifications subject to change without notice

OPTIONAL ACCESSORIES



**ATN X-TRAC 5
REMOTE CONTROL**



ATN X-SOUND



**ATN WEAPON
BATTERY PACK**




**ATN LP QUICK
DETACH MOUNT**



THOR 5 XD / 5 XD LRF SERIES

1280X1024 GEN 5 THERMAL SCOPE



*scope view

XD 1280X1024 THERMAL SENSOR

Offers unparalleled detail from a distance, with a million more pixels than competitors for superior image quality, day or night.

RETICLE CUSTOM RETICLE EDITOR

Design and share unique reticles using the ATN Custom Reticle Editor for personalized hunting experiences.

LRF BUILT-IN LASER RANGEFINDER (OPTIONAL)

Achieve pinpoint accuracy and ensure every shot counts, regardless of the distance to your target.

HD VIDEO HD VIDEO RECORDING

Capture your hunting trips in high-definition, reliving each moment with clear, crisp video quality.

BC ADVANCED BALLISTIC CALCULATOR

Tailor each shot to environmental conditions, ensuring accuracy in any setting.

EF ENHANCED HUNTING FEATURES

Includes One Shot Zero, Profile Manager, Recoil Activated Video (RAV), and extended battery life, making it an ideal scope for any hunting scenario.



SPECIFICATIONS

Model	ThOR 5 XD			ThOR 5 XD LRF		
	ThOR 5 XD 2-20x	ThOR 5 XD 3-30x	ThOR 5 XD 4-40x	ThOR 5 XD LRF 2-20x	ThOR 5 XD LRF 3-30x	ThOR 5 XD LRF 4-40x
Item #	TIWST51250A	TIWST51275A	TIWST51210A	TIWST51250LRF	TIWST51275LRF	TIWST51210LRF
Laser Rangefinder	No			Yes		
Sensor	1280x1024 60 fps 12 µm					
Magnification	2-20×	3-30×	4-40×	2-20×	3-30×	4-40×
Field of view, degrees	17.6x13.2	11.8x8.8	8.8x6.6	17.6x13.2	11.8x8.8	8.8x6.6
Core	ATN Gen V Quad Core T					
Eye relief	90 mm					
Video Record Resolution	Up to 1280x960 @ 60 fps					
Ballistic Calculator	Yes					
WiFi (Streaming, Gallery, & Controls)	iOS & Android					
Bluetooth	Yes					
3D Gyroscope	Yes					
3D Accelerometer	Yes					
RAV (Recoil Activated Video)	Yes					
Electronic Compass	Yes					
Smooth Zoom	Yes					
Radar	Yes					
Reticles	Multiple Patterns & Color Options, User Custom reticles					
Reticle Editor	Yes					
Microphone	Yes					
MicroSD card	4 to 64 Gb					
USB, type C	Yes					
Mount	30 mm Standard Rings (included)					
Battery life (Li-ion)	10 hrs					
Waterproof rating / IP rating	Weather resistant					
Human Detection Range	2150	3200	4000	2150	3200	4000
Human Recognition Range	860	1440	1800	860	1440	1800
Human Identification Range	480	610	720	480	610	720
Operating Temperature	-20°F to +120°F / -28°C to 48°C					
Dimensions	14.4"x2.9"x2.9" 365x73x73 mm	15.5"x2.9"x2.9" 395x73x73 mm	16.7"x2.9"x2.9" 425x73x73 mm	14.4"x2.9"x2.9" 365x96x73 mm	15.5"x2.9"x2.9" 395x96x73 mm	16.7"x2.9"x2.9" 425x96x73 mm
Weight	2.5 lb / 1.133 kg			2.7 lb / 1.203 kg		
Warranty	3 years					

*Specifications subject to change without notice

OPTIONAL ACCESSORIES



ATN X-SOUND



**ATN X-TRAC 5
REMOTE CONTROL**



**ATN HP QUICK
DETACH MOUNT**






**ATN THERMAL
TARGETS (SET OF 3)**





THOR LTV SERIES

ULTRA LIGHT THERMAL RIFLE SCOPE



ADVANCED 60 HZ THERMAL SENSOR

Delivers clear imagery in challenging conditions and smooth videos with minimal distortion.

VIDEO RECORDING

Enables capturing memorable hunting moments, shareable with friends and family.

BLACK HOT/WHITE HOT AND COLOR MODES

Provides versatile imaging options to enhance visibility and target distinction in various conditions.

ONE SHOT ZERO

Simplifies zeroing with a single shot; adjust the reticle to the first impact point for accuracy.

LIGHTWEIGHT DESIGN AND EASY MOUNTING

Makes the ThOR LTV suitable for various hunting scenarios and compatible with multiple platforms.





SPECIFICATIONS

	ThOR LTV 160		ThOR LTV 256				ThOR LTV 320			ThOR LTV 640		
Item #	TIWSTLTV112X	TIWSTLTV119X	TIWSTLTV212X	TIWSTLTV219X	TIWSTLTV225X	TIWSTLTV235X	TIWSTLTV319X	TIWSTLTV325X	TIWSTLTV335X	TIWSTLTV625X	TIWSTLTV635X	TIWSTLTV650X
Resolution	160x120 px / 12 µm		256x192 px / 12 µm				320x240 px / 12 µm			640x480 / 12 µm		
Magnification	3-9x	5-15x	1.5-4.5x	2-6x	3-9x	4-12x	3-9x	4-12x	5-15x	2-6x	3-9x	4-12x
Field of view	8.7°x6.5°	6.2°x4.7°	14.2°x10.7°	8.9°x6.7°	7.1°x5.4°	4.9°x3.7°	11.6°x8.7°	8.8°x6.6°	6.3°x4.7°	17.6°x13.2°	12.6°x9.4°	8.8°x6.6°
Display Resolution	1280x720 px		1024x768 px									
Eye relief	90 mm											
Video Record Resolution	1024x768 px											
3D Accelerometer	Yes											
Color modes	White Hot/Black Hot/Color Modes											
Reticles	Multiple Patterns											
Micro SD card	4 to 64 GB											
USB, type C	Yes											
Mount	30 mm Standard Rings (not included)											
Internal Lithium Ion Battery	9 + hrs											
IP rating	Weather resistant											
Human Detection Range	475 y/m	625 y/m	515 y/m	825 y/m	1035 y/m	1500 y/m	715 y/m	910 y/m	1510 y/m	740 y/m	920 y/m	1670 y/m
Human Recognition Range	240 y/m	315 y/m	130 y/m	210 y/m	260 y/m	375 y/m	305 y/m	455 y/m	680 y/m	375 y/m	485 y/m	700 y/m
Human Identification Range	160 y/m	210 y/m	65 y/m	105 y/m	130 y/m	190 y/m	200 y/m	290 y/m	400 y/m	250 y/m	325 y/m	440 y/m
Dimensions	292x56x55 mm / 11.5" x 2.2" x 2.2"											
Weight	1.4 lb / 650 g											
Warranty	3 years											

*Specifications subject to change without notice.

OPTIONAL ACCESSORIES



ATN X-SOUND



ATN WEAPON BATTERY PACK




ATN QUICK DETACH MOUNT



TICO LTV SERIES

THERMAL CLIP-ON



TRANSFORMS DAYTIME SCOPE TO THERMAL IMAGING

Upgrades standard optics to thermal vision effortlessly.

HIGH-RESOLUTION THERMAL IMAGING

Delivers clear, detailed views in thermal mode, improving night-time hunting and observation.

MULTIPLE VIEWING MODES

Includes black hot, white hot, and color modes, allowing for adaptable viewing based on personal preference.

EASY-TO-MOUNT FEATURE

Enables capturing of hunting experiences across night vision, thermal, and combined modes.

LIGHTWEIGHT CONSTRUCTION

Designed for comfort during extended use without adding excess weight to your equipment.

ULTRA-LOW POWER CONSUMPTION

Offers up to 9 hours of operation, making it ideal for long hunting trips or observations.



SPECIFICATIONS

	ATN TICO LTV 256 1x	ATN TICO LTV 320 1x	ATN TICO LTV 640 1x
Item #	TICOLTV225X	TICOLTV325X	TICOLTV650X
Sensor	ATTO 320, 12µm		ATTO 640, 12µm
Objective lens	25 mm	25 mm	50 mm
Resolution	320x240		640x480
Magnification	1-4x		
Field of view, degrees	8.8 (H) x 6.6 (V)		
Display Resolution	OLED 1024x768		
Eye relief	Unlimited		
Color modes	10 palletes		
Monocular mode	Yes		
Digital zoom	2x, 4x		
Mount	Modular adapter or QDM		
Battery (Li-ion)	1 cell 18650, removable.		
Battery life	8 hours		
Waterproof rating / IP rating	Weather resistant		
Operating temperature	-4°F to +120°F / -20°C to 48°C		
Detection Range	835 y/m	1040 y/m	2080 y/m
Recognition Range	210 y/m	260 y/m	520 y/m
Identification Range	105 y/m	130 y/m	260 y/m
Dimensions	5.2" x 2.4" x 3.1" / 132x60x78 mm		5.2" x 2.4" x 3.1" / 152x60x78 mm
Weight	0.9 lbs / 400 g	0.9 lbs / 400 g	1.0 lbs / 470 g
Warranty	2 years		

*Specifications subject to change without notice.

**When choosing to use this option, the incorporation of your widgets are absent. Widgets would include reticle, time stamp, and logo that are added during video processing.

OPTIONAL ACCESSORIES



ATN X-SOUND



ATN THERMAL TARGETS (SET OF 3)





ODIN LT SERIES

COMPACT THERMAL MONOCULAR



*scope view



ATN'S OBSIDIAN LT CORE

Powers a hands-free, compact, and ergonomic thermal monocular for an exceptional observation experience, even at night.

HIGH-RESOLUTION DISPLAY

Ensures the images you view are clear and vivid, enhancing the overall observation quality.

WHITE HOT/BLACK HOT MODE

Offers the option to display moving objects in your chosen color palette for enhanced visibility.

VERSATILE MOUNTING OPTIONS

Can be used hand-held, helmet-mounted, or head-mounted for comfortable, long-term observation.

COMPACT DESIGN

Small enough to fit in one hand, offering ease of use and quick menu access.

SPECIFICATIONS


	ODIN LT 320 2-4x	ODIN LT 320 3-6x	ODIN LT 320 4-8x	ODIN LT 640 1-4x	ODIN LT 640 2-8x	ODIN LT 640 3-12x
SKU	TIMNODN319X	TIMNODN325X	TIMNODN335X	TIMNODN619X	TIMNODN625X	TIMNODN635X
Resolution	320x240, 60 fps, 12 μm			640x480, 60 fps, 12 μm		
Magnification	2-4x	3-6x	4-8x	1-4x	2-8x	3-12x
Field of view	11.6°x8.7°	8.8°x6.6°	6.3°x4.7°	23.2°x17.4°	17.6°x13.2°	12.6°x9.4°
Core	ATN Obsidian Core LT					
Display Resolution	1280x960 px					
Eye relief	25 mm					
Color modes	White Hot / Black Hot					
Battery type	1 x CR123A (Li-ion)					
Battery life (Li-ion)	2.5 Hrs (or Optional Rechargeable Battery with 5 Hrs of runtime)					
Charging	USB, type C port is on the Optional Rechargeable Battery					
IP rating	Weather resistant					
Human Detection Range	535 m	910 m	1510 m	715 m	1250 m	1580 m
Human Recognition Range	380 m	455 m	680 m	445 m	580 m	720 m
Human Identification Range	230 m	290 m	340 m	260 m	320 m	350 m
Operating Temperature	-20°F to +120°F / -28°C to 48°C					
Dimensions	5.16"x2.8"x1.81" / 131x71x46 mm		5.71"x2.8"x2.01" 145x71x51 mm	5.16"x2.8"x1.81" / 131x71x46 mm		5.71"x2.8"x2.01" 145x71x51 mm
Weight	285 g		342 g	285 g		342 g
Warranty	3 years					

*Specifications subject to change without notice

OPTIONAL ACCESSORIES



EXTENDED LIFE BATTERY PACK



ATN NOROTOS HELMET MOUNT



UNIVERSAL HEADSET MOUNT




4K+
SENSOR

SMART HD
OPTICS

5
GEN

BINOX 5 5-25X

ULTRA HD 4K+ DAY/NIGHT VISION BINOCULARS W/ LASER RANGEFINDER



4K+ ULTRA HD 4K+ SENSOR W/ ENHANCED NIGHT VISION

Offers industry-leading resolution and superior night vision for clear images in any conditions over long distances.

L BUILT-IN LASER RANGEFINDER

Provides accurate distance measurements up to 1000 yards/meters, functional in both day and night settings.

BIX BALLISTIC INFORMATION EXCHANGE (BIX)

Enables seamless integration with other ATN scopes and traditional glass scopes via the ATN Laser Ballistics app.

4K VIDEO 4K VIDEO RECORDING

Captures adventures in stunning 4K resolution with detailed 240 FPS slow-motion playback.

B LONG-LASTING BATTERY W/ SMART PROXIMITY SENSOR

Offers up to 12 hours of use with efficient power management w/ Smart Proximity Sensor.

SPECIFICATIONS

	BinoX 5 5-25x
Item #	DGBNBN5LRF
Sensor	ATN 4K 4056x3040 30/60/120 FPS
Magnification	5-25x
Angle of view	5°
Field of view @ 1000 yards	87.5 yards
Objective lens	60 mm
Display Resolution	1280x960p
Interpupillary adjustment range	60-70 mm
Eye relief	10-30 mm
IR illuminator	Yes
Precision to	± 1 y/m
Focus Range	10 ft - ∞
Laser Range Finder	Yes
Micro HDMI output	Yes
Electronic Image Stabilization (EIS)	Yes
Video Record Resolution	Up to 4K UHD (30/60/120 fps)
IP rating	Weather resistant
Charging	USB, type C
WiFi (Streaming, Gallery, & Controls)	iOS & Android
Bluetooth	Yes
3D Accelerometer	Yes
3D Gyroscope	Yes
E-Compass	Yes
Smooth Zoom	Yes
Night Vision Mode	Yes
Micro SD Card	Yes
Operating Temperature	-20°F to +120°F / -28°C to 48°C
Battery life (Li-ion)	Up to 12 hours
Dimensions	7.8"x6.7"x3" / 197x171x76 mm
Weight	3.15 lb / 1.43 kg
Warranty	2 years

*Specifications subject to change without notice.

OPTIONAL ACCESSORIES



**ATN EXTENDED
LIFE BATTERY KIT**



**SANDISK EXTREME
64GB MICROSDXC**





10X42 LRF SERIES

LASER RANGEFINDING BINOCULARS



10x 10X MAGNIFICATION

Offers powerful zoom for detailed target identification.

ADVANCED LASER RANGEFINDER

Combines high-quality binocular vision with a state-of-the-art rangefinder.

ENHANCED OLED RED DISPLAY

Delivers a brighter image and improved color quality for clear viewing.

PROSHIELD AND EVER-LIGHT LENS COATINGS

Ensures maximum light transmission and optical clarity in various lighting conditions.

BIX WITH FREE LASER BALLISTIC APP

Ballistic Information Exchange system compatible with a free, downloadable app for iOS and Android, enhancing shooting accuracy.

RUBBER ARMOR WITH SHOCKPROOF DESIGN

Capture crucial moments with stunning clarity at 240 frames per second.

SPECIFICATIONS

	10x42 LRF 2000	10x42 LRF 3000
Item #	BN1042LRF2K	BN1042LRF3K
LRF Range	5-2000 m	5-3000 m
Accuracy	±1 m (y)	
Magnification	10x	
Objective lens effective diameter	42 mm	
Field of view	7°	
Focus System	Fixed/Focus Free	
Focus Range	10 m (y) to infinity	
Eye Relief	16 mm	
Exit pupil diameter	3.3 mm	
Diopter adjustment range	±5 diopters	
Display	High transmission, OLED	
Optical coatings	Multi-layer coating	
LRF laser wavelength	905 nm	
Bluetooth	Yes	
Body material	ABS plastic and rubber	
Waterproof	IPX6	
Battery	CR2 (3 V)	
Compatibility	Android and iOS apps, ATN Mars 4, Mars 5, ThOR 4, ThOR 5, X-Sight 4K Pro, X-Sight 5 rifle scope series	
Dimensions L x W x H	5.7"x5.1"x2.36" / 145x129x60 mm	
Weight with caps and battery	25.6 oz / 725 g	
Warranty	2 years	

*Specifications subject to change without notice.

OPTIONAL ACCESSORIES




**DELUXE
BINOCULARS BAG**





BINOX 4T SERIES

SMART HD THERMAL BINOCULARS W/ BUILT-IN LASER RANGEFINDER



*scope view



NEXT GEN THERMAL SENSOR

Offers exceptional clarity and detail, ensuring precise target identification in various lighting conditions.

HD VIDEO RECORDING

Efficiently captures your experiences in high-definition, enabling vivid playback and easy sharing of your adventures.

LASER RANGEFINDER

Perfect for varied uses like hunting, sports, surveillance, and golfing, providing quick and accurate distance measurements at the press of a button.

LOW POWER CONSUMPTION

Offers more than 16 hours of continuous operation, ideal for long-duration outdoor activities where charging options are limited.

ADAPTABLE INTERPUPILLARY ADJUSTMENT

Allows for adjustable lens spacing and includes comfortable eye support, ensuring a tailored and fatigue-free viewing experience.

SPECIFICATIONS

	BinoX 4T 1.25-5x	BinoX 4T 2-8x	BinoX 4T 4.5-18x	BinoX 4T 1-10x	BinoX 4T 1.5-15x	BinoX 4T 2.5-25x
Item #	TIBNBX4381L	TIBNBX4382L	TIBNBX4384L	TIBNBX4641L	TIBNBX4642L	TIBNBX4643L
Sensor	384x288			640x480		
Magnification	1.25-5x	2-8x	4.5-18x	1-10x	1.5-15x	2.5-25x
Field of view	16°x12.5°	12°x9.5°	6x4.7°	32°x25°	24°x19°	12.5°x9.7°
Display Resolution	1280x720x2 px					
Interpupillary adjustment range	60-70 mm					
Eye relief	10-30 mm					
Focus Range	10 ft to infinity					
Laser Rangefinder	Yes					
Precision to	± 1 y/m					
Range	5-1000 y/m					
Video Record Resolution	Up to 1280x960p @ 30/60fps					
IP rating	Weather Resistant					
Charging	USB, type C					
WiFi (Streaming, Gallery, & Controls)	iOS & Android					
Micro SD Card	4 to 64 GB					
Battery life (Li-ion)	15+ hrs					
Human Detection Range	750 m	960 m	1800 m	830 m	1050 m	1950 m
Human Recognition Range	335 m	480 m	720 m	350 m	530 m	800 m
Human Identification Range	205 m	300 m	430 m	225 m	330 m	475 m
Dimensions	9.4" x 5" x 2.6" / 240 x 128 x 67 mm					
Weight	2.5 lb / 1.12 kg					
Warranty	3 years					

*Specifications subject to change without notice

OPTIONAL ACCESSORIES



**ATN EXTENDED
LIFE BATTERY KIT**



**SANDISK EXTREME
64GB MICROSDXC**



**DELUXE
BINOCULARS BAG**





4K+
SENSOR

SMART HD
OPTICS

5
GEN

X-SPOTTER 5 20-100X

ULTRA HD 4K+ DAY/NIGHT SPOTTING SCOPE



4K ULTRA 4K SENSOR

Delivers high-resolution imaging for sharp, detailed views in both daytime and nighttime conditions.

INTUITIVE USER INTERFACE

Offers a user-friendly experience with comprehensive features such as E-compass, Pitch and Yaw angles, and Ballistic corrections.

ENHANCED IMAGE STABILIZATION

Features a built-in gyroscope and image stabilization technology for smooth and steady viewing.

ADVANCED ENVIRON- MENTAL SENSORS

Includes GPS, barometer, gyroscope, and more for accurate data collection and navigation. Integrated with E-Compass and 3D Magnetometer for precise orientation.

4K VIDEO RECORDING

Allows recording in Real 4K quality, ideal for capturing and sharing your outdoor adventures.

ULTRA-LOW POWER CONSUMPTION

Ensures up to 14 hours of continuous operation, making it suitable for extended outdoor activities.

SPECIFICATIONS

	X-Spotter 5 20-120x
Item #	DGSSX52080
Sensor	ATN 4K+ 4056x3040 30/60/120 FPS
Magnification	20-100x
Field of view, degrees	1.7
Field of view, m	3 m / 100m
Core	ATN Gen V Quad Core
Micro Display	1280x960
Eye relief	10-30 mm
Focus Range	10 ft - ∞
Video Record Resolution	Up to 4K UHD (30/60/120 fps)
WiFi (Streaming, Gallery,& Controls)	iOS, Android
Bluetooth	Yes
3D Gyroscope	Yes
3D Accelerometer	Yes
Electronic Compass	Yes
Smooth Zoom	Yes
Night Vision mode	Yes
Microphone	Yes
Digital Image Stabilization (EIS)	Yes
MicroSD card	4 to 64 Gb (V30 class)
HDMI over USB	Yes
USB, type C	Yes
Battery life (Li-ion)	Up to 14 hours
Waterproof rating / IP rating	Weather resistant
Operating Temperature	-20°F to +120°F / -28°C to 48°C
Dimensions	15.6"x4.3"x3.3" / 395x110x84 mm
Weight	3,2 lb / 1450 g
Warranty	2 years

*Specifications subject to change without notice.

**When choosing to use this option, the incorporation of your widgets are absent. Widgets would include reticle, time stamp, and logo that are added during video processing.

OPTIONAL ACCESSORIES



**ATN X-TRAC 5
REMOTE CONTROL**




**ATN HP QUICK
DETACH MOUNT**



NVM14 SERIES

NIGHT VISION MULTI-PURPOSE SYSTEM



FEATURES

- HEAD OR HELMET MOUNTABLE FOR HANDS-FREE USAGE
- ERGONOMIC, SIMPLE, EASY TO OPERATE CONTROLS
- WEAPON MOUNTABLE
- COMPACT, RUGGED DESIGN
- AUTOMATIC BRIGHTNESS CONTROL
- WATERPROOF
- BUILT-IN INFRARED ILLUMINATOR

OPTIONAL ACCESSORIES



ATN 3X LENS



ATN 5X LENS



ATN PIACCANTINY MOUNT ADAPTER



ATN DUAL BRIDGE

SPECIFICATIONS

Total darkness IR system	Yes
Magnification	1x
Lens System	F1.2, 27 mm
Proshield lens coating	Yes
FOV	40°
Range of focus	0.25 yd/m to infinity
Diopter adjustment	-6 to +2
Controls	Direct
Automatic brightness control	Yes
Bright light cut-off	Yes
Infrared illuminator	Built-in
Infrared indicator	Yes
Low battery indicator	Yes
Power supply	1x3v CR123A or 1 AA
Battery life	50 (CR123A) or 30 (AA) hours
Environmental rating	Waterproof
Operating temperature	-40°F to +122°F / -40°C to +50°C
Storage temperature	-58°F to +158°F / -50 to +70 °C
Dimensions	4.7" x 1.9" x 2.7" / 120 x 49 x 69 mm
Weight	0.75 lbs / 0.34 kg
Warranty	2 years

ITEM #	MODEL NAME	TUBE CONFIGURATION
NVMPAN142G	ATN PVS14-2G	Gen. 2*
NVMPAN142W	ATN PVS14-2W	Gen. 2*
NVMPAN14HPG	ATN PVS14-HPT	Gen. 2+ GP*
NVMPAN14HPW	ATN PVS14-HPT	Gen. 2+ WP*

* No Export Available

ACCESSORY PACKAGES FOR ATN PVS14

ACMPAN14LS3A	ATN 3x lens A-Focal
ACMPAN14LS05	ATN 5x lens A-Focal
ACMPAN14PCWM	ATN Piaccantiny mount adapter
ACMPAN14DB	ATN Dual Bridge

PVS14 SERIES

NIGHT VISION MULTI-PURPOSE SYSTEM



ITEM #	MODEL NAME	TUBE CONFIGURATION
NVMPPVS142G	ATN PVS14-2	Gen. 2 GP*
NVMPPVS142W	ATN PVS14-2	Gen. 2 WP*
NVMPPVS14HPG	ATN PVS14-HPT	Gen. 2 GP*
NVMPPVS14HPW	ATN PVS14-HPT	Gen. 2 WP*
NVMPPVS143WHP	ATN PVS14-3WHPT	Gen. 3WHPT*
NVMPPVS143HFW	ATN PVS14-3HFW	Gen. 3HFW*
NVMPPVS1452G	ATN PVS14-2	Gen. 2*
NVMPPVS1452W	ATN PVS14-2, 51 FOV	Gen. 2WP*
NVMPPVS145HPG	ATN PVS14-HPT, 51 FOV	Gen. 2+*
NVMPPVS145HPW	ATN PVS14-HPT, 51 FOV	Gen. 2+*
NVMPPVS1453WHP	ATN PVS14-3WHPT	Gen. 3WHPT*
NVMPPVS1453HFW	ATN PVS14-3HFW, 51 FOV	Gen. 3HFW*

* No Export Available

FEATURES

- MIL-STD-810
- LIGHTWEIGHT
- 1X MAGNIFICATION
- BRIGHTNESS CONTROL
- BRIGHT LIGHT CUT-OFF
- WATERPROOF
- HANDHELD OR HEAD-MOUNTED AS SINGLE EYE GOGGLE

SPECIFICATIONS

Total darkness IR system	Yes
Magnification	1x
Lens System	F1.2, 27 mm
Proshield lens coating	Yes
FOV	40°/51°
Range of focus	0.25 yd/m to infinity
Diopter adjustment	-5 to +2
Controls	Direct
Automatic brightness control	Yes
Bright light cut-off	Yes
Infrared illuminator	Built-in
Infrared indicator	Yes
Low battery indicator	Yes
Power supply	1 x 1.5V (AA type battery)
Battery life	50 hours
Environmental rating	Waterproof
Operating temperature	-60°F to +120°F / -51°C to +49°C
Storage temperature	-60°F to +185°F / -51 to +85 °C
Dimensions	4.5" x 2.2" x 2" / 114 x 56 x 50 mm
Weight	0.75 lbs /0.34 kg
Warranty	2 years

ACCESSORY PACKAGES FOR ATN PVS14

ACMUHMNTMICH	ATN MICH Helmet Mount Assembly USA	ACMPPVSXL5A	ATN 5x Mil-Spec Magnifier Lens
ACMUHMNTPAGS	ATN PAGST Helmet Mount Assembly USA	ACMPPVSXWM01	ATN Weapon Mount (PVS14)
ACMPPVSXL3A	ATN 3x Mil-Spec Magnifier Lens	ACMPPV14DB	Dual Bridge

NVG7 SERIES

NIGHT VISION GOGGLES




ITEM #	MODEL NAME	TUBE CONFIGURATION
NVGONVG72G	NVG7-2G	Gen. 2+*
NVGONVG72W	NVG7-2W	Gen. 2+*

* No Export Available


ACCESSORY PACKAGES FOR ATN PVS14

ACGONVG75X	5x Magnifier Lens
ACGONVG78X	8x Magnifier Lens

OPTIONAL ACCESSORIES



**ATN X-TRAC 5
REMOTE CONTROL**



**ATN HP QUICK
DETACH MOUNT**

FEATURES

- LIGHTWEIGHT, COMPACT RUGGED GOGGLE SYSTEM
- MULTI-PURPOSE: HAND-HELD, HEAD-MOUNTED OR HELMET-MOUNTED
- COMFORTABLE, FLIP-UP HEADGEAR
- MULTI-COATED ALL-GLASS OPTICS
- WIDE ANGLE INFRARED ILLUMINATOR
- HEAD MOUNT INCLUDED
- ADJUSTABLE INTERPUPILLARY DISTANCE
- OPTIONAL 5X AND 8X LENSES AVAILABLE

SPECIFICATIONS

Total darkness IR system	Yes
Magnification	1x
Lens System	F1.2, 26 mm
Proshield lens coating	Yes
FOV	40°
Range of focus	1 yd/m to infinity
Diopter adjustment	-6 to +2
Controls	Direct
Automatic brightness control	Yes
Bright light cut-off	Yes
Infrared illuminator	Built-in
Infrared indicator	Yes
Low battery indicator	Yes
Power supply	1 x 3V (CR123A)
Battery life	60 hours
Environmental rating	Waterproof
Operating temperature	-40°F to +122°F / -40°C to +50°C
Storage temperature	-58°F to +158°F / -50 to +70 °C
Dimensions	6.3" x 6" x 3" / 160 x 150 x 75 mm
Weight	1.1 lbs /0.5 kg
Warranty	2 years

PVS7 SERIES

NIGHT VISION GOGGLES



ITEM #	MODEL NAME	TUBE CONFIGURATION
NVGOPVS7HP	PVS7-HPT	Gen. 2+*
NVGOPVS7W0	PVS7-WPT	Gen. 2+*

* No Export Available

ACCESSORY PACKAGES FOR ATN PVS14	
ACMPPVSL3A	ATN 3x Mil-Spec Magnifier Lens
ACMPPVSL5A	ATN 5x Mil-Spec Magnifier Lens

FEATURES

- HANDHELD, HEAD-MOUNTED OR HELMET-MOUNTED
- WATERPROOF
- USE TWO AA TYPE BATTERY
- 1X MAGNIFICATION
- STANDARD MILITARY ISSUE
- COMBAT PROVEN
- ONE-KNOB OPERATION
- BUILT-IN INFRARED ILLUMINATOR

OPTIONAL ACCESSORIES



**ATN X-TRAC 5
REMOTE CONTROL**




**ATN HP QUICK
DETACH MOUNT**

SPECIFICATIONS

Total darkness IR system	Yes
Magnification	1x
Lens System	F1.2, 26 mm
Proshield lens coating	Yes
FOV	40°
Range of focus	1 yd/m to infinity
Diopter adjustment	-6 to +2
Controls	Direct
Automatic brightness control	Yes
Bright light cut-off	Yes
Infrared illuminator	Built-in
Infrared indicator	Yes
Low battery indicator	Yes
Power supply	1 x 3V (CR123A)
Battery life	60 hours
Environmental rating	Waterproof
Operating temperature	-40°F to +122°F / -40°C to +50°C
Storage temperature	-58°F to +158°F / -50 to +70 °C
Dimensions	6.3" x 6" x 3" / 160 x 150 x 75 mm
Weight	1.1 lbs /0.5 kg
Warranty	2 years

PS31 SERIES

NIGHT VISION GOGGLES



ITEM #	MODEL NAME	TUBE CONFIGURATION
NVGOPS3142G	ATN PS31-2 GP	Gen. 2+*
NVGOPS3142W	ATN PS31-2 WP	Gen. 2+*
NVGOPS314HPG	ATN PS31-HPT GF	Gen. 2+*
NVGOPS314HPW	ATN PS31-HPT WP	Gen. 2+*
NVGOPS3143HPW	ATN PS31-3HFW GF	Gen. 3*
NVGOPS3143HFW	ATN PS31-3HFW WP	Gen. 3WPT*
NVGOPS3152G	ATN PS31-2, 51 FOV, GP	Gen. 3*
NVGOPS3152W	ATN PS31-2, 51 FOV, WP	Gen. 2+*
NVGOPS315HPG	ATN PS31-HPT, 51 FOV, GP	Gen. 2+*
NVGOPS315HPW	ATN PS31-HPT, 51 FOV, WP	Gen. 2+*
NVGOPS3153HPW	ATN PS31-3HFW, 51 FOV, GP	Gen. 3*
NVGOPS3153HFW	ATN PS31-3HFW, 51 FOV, WP	Gen. 3*

* No Export Available

ACCESSORY PACKAGES FOR ATN PVS14

ACGOPS31LS3P	Set 3x lenses
ACMUHMNTDVTL	Dovetail helmet mount USA


FEATURES

- DUAL IMAGE INTENSIFIER TUBES
- MIL-SPEC HIGH-RESOLUTION OPTICS
- ADJUSTABLE INTERPUPILLARY DISTANCE
- MULTI-COATED LENSES
- BUILT-IN INFRARED (IR) ILLUMINATOR
- WATERPROOF AND SHOCKPROOF
- LONG-LASTING BATTERY LIFE
- MANUAL GAIN CONTROL

SPECIFICATIONS

Total darkness IR system	Yes
Magnification	1x
Lens System	19 mm, F/1.26
Proshield lens coating	Yes
FOV	40° / 51°
Range of focus	0.25 yd/m to infinity
Diopter adjustment	-6 to +2 diopters
Manual Gain Control	Yes
Interpupillary Distance	54 to 88 mm
Bright light cut-off	Yes
Infrared illuminator	Yes
Power supply	(1) CR123A
Battery life	≥ 20 hrs. on (1) CR123A lithium battery
Environmental rating	
Operating temperature	-40° to +122°F / -40° to +50°C
Storage temperature	-58° to +158°F / -50° to +70°C
Dimensions	4.4" x 4.15" x 3.4" / 112x105x86 mm
Weight	1.28 lb /580 g
Warranty	2 years

IR850 PRO LONG RANGE INFRA-RED ILLUMINATOR



ATN IR850 Pro an extremely powerful, long range 850 mW infrared illuminator for hunting and search and rescue use.

IR850 SUPERNOVA EXTREME RANGE INFRA-RED ILLUMINATOR



ATN IR850 Supernova; an extremely powerful, long range infra-red illuminator with adjustable mount, that is perfect for hunting and search and rescue use.

IR940 LONG RANGE INFRA-RED ILLUMINATOR



The IR940 IR illuminator provides a more covert experience when you want to stay hidden from your prey. Animals and people are not able to see the red glow when looking at the illuminator, even at the light source.

POWER WEAPON KIT 20,000 mAh BATTERY PACK



The ATN Extended Power Kit gives you plenty of juice whenever and wherever you need it. Up to 20 hrs of continuous use. Easy to recharge and can power other devices.

Designed to be used with the ATN line of Smart HD Optics: X-Sight 4K, ThOR 4, X-Sight 5, ThOR 5, ThOR LTV.

EXTENDED LIFE BATTERY KIT 10,000 mAh BATTERY PACK



Don't let yourself be stuck without a functioning unit, because you didn't bring extra batteries to power your device. ATN Extended Life Battery kit can support your binoculars or monoculars for up to 15 hrs. You can use your devices longer and save money and the environment in the process. Enjoy your activities all day long — whether scouting, camping, bird watching, or surveillance. You can even power your none ATN devices, which are compatible with a micro USB.


Designed to be used with the ATN line of Smart HD Optics: BinoX 4K and BinoX 4T.

X-TRAC 5



Use the X-TRAC 5 to connect to your Gen 5 products and have the ultimate control over your device. Adjust settings and activate functions.

TACTICAL CARRY CASE



The ATN Tactical Carry Case is a great addition to protect your investment. These carry cases are made out of high quality material with molle webbing and attachments to connect to your loadout gear or compatible backpack, chest rig or harness. Our tactical bags are perfect for the ATN OTS XLT and OTS LT models. Keep your tactical gear protected while out and about in the field.

DELUXE BINOCULARS BAG



The ATN Deluxe Binoculars Bag is a comfortable and ergonomic bag with plenty of storage space for your BinoX 4K/4T and or OTS LT/4T units. Plus have easy access to your device and or needed accessories while in the field. Plenty of pockets and mesh webbing, for cables, batteries, power banks, auxiliary illuminators or cell phone.

LOW PROFILE QUICK DETACH HEAVY DUTY MOUNT




The Low Profile Quick Detach Mount (LPQDM) is designed specifically to be used with the X-Sight 5, X-Sight LTV, ThOR LT, ThOR LTV and ThOR 5 640 Series of scopes. The LPQDM allows you to quickly switch your scope between rifles; allowing you to take full advantage of the 6 different profiles you can utilize in your Smart HD scope. Simple to install and use, the quick detach mount provides a way for you to swap weapons easily, all while retaining zero.

QUICK DETACH MOUNT



The ATN Quick Detach Mount is a great addition for your new X-Sight 4K or ThOR 4. Take advantage of the profile manager of your scope, move it from platform to platform and still retain zero.

THERMAL TARGETS



The ATN Thermal Targets are a great and easy way to Zero in your Thermal Scope, eliminating the frustration of finding a hot or cold target. It uses special material with an included heat source to give you a thermal signature that is easily picked up by your thermal scope.

HIGH PROFILE QUICK DETACH HEAVY DUTY MOUNT



The High Profile Quick Detach Mount (HPQDM) is designed specifically to be used with the X-Sight 4K, ThOR 4 and ThOR 5 640/XD Series of scopes. The HPQDM allows you to quickly switch your scope between rifles; allowing you to take full advantage of the 6 different profiles you can utilize in your Smart HD scope. Simple to install and use, the quick detach mount provides a way for you to swap weapons easily, all while retaining zero.

THERMAL COYOTE/BOAR TARGET KIT



The innovative Coyote and Boar Thermal Targets lets you practice usage of your device. The pasters allow you to reuse the targets and get the most out of the package. Universal Thermal Target to get your scope Zeroed and Ready to go quickly. Coyote or Boar Thermal Target size – 30" x 24".

X-SOUND HEARING PROTECTOR



ATN X-Sound reduces harmful loud noise down to safe levels below 82 dB and enhances clarity of surrounding low level sounds such as conversations and announcements.

The ergonomic volume control knob allows for total adjustment of the two built-in omni directional microphones, while built-in wireless capability enables hands-free calling and music enjoyment. Or, connect a playing device via the 3.5 mm audio jack.



AMERICAN TECHNOLOGIES NETWORK CORP.
2400 NW 95 Ave, Doral, FL 33172

Direct Sales: 305-900-6841
Customer Service: 650-989-5100
TOLL FREE **800-910-2862**

info@atncorp.com

www.atncorp.com

The products in this catalog are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.