

NIGHT VISION GOGGLES

ATN PVS-7 is a full robust, dependable, high performance night visiongoggle. This model is identical to AN/PVS-7 model adopted as a standard issue to US Army ground troops and designed to assist viewing and provide reliable service in the most unfavorable conditions. The ATN PVS-7 also incorporates an infrared illuminator with a momentary and continuous on switching function. Infrared operation and low battery indicators are displayed within the user's field of view. The ATN PVS-7 comes complete with a lightweight, fully adjustable military head strap that allows for comfortable long-term use. Full U.S.Mil Spec body with goggle assembly, soft carrying case, demist shield, sacrificial filter for objective lenses, shoulder strap, head mount assembly with 3 brow pads, lens tissue, neck cord and front lens cap.

STANDARD ACCESSORIES include:

- Flip-up Head Mount Assembly Allows for hands-free operation
- Medium & Thick Brow Pads Changeable pads for secure head mount fit
- **Eye Cups** Prevents the emission of stray light or facial reflections
- **Soft Carrying Case** Provides convenient storage
- **Shoulder Strap** Attached to the PVS-7 carrying case for easy portability
- Lens Paper Used to safely clean the objective and eyepiece glass surfaces
- Day Light Filter Filters excessive light. Protects objective lens from the elements
- Sacrificial Window Shields the optics from sand, air particles, or anything that may scratch the lens
- Demist Shields Snaps onto the eyepiece to prevent condensation from forming on the optics
- Operator's Manual Instructional user's guide
- Batteries Two (2) AA



PVS7-CGT

- Standard Military Issue
- Multi-purpose: Handheld, head-mounted, helmet-mounted
- Lightweigh
- Equipped with momentary or continuous IR switch
- Internal low battery and IR indicators
- Combat proven
- Water and fog resistant
- Limited Two-Year Warranty

SPECIFICATIONS

Magnification	1x	
Lens System	F1.2, 27mm	
Proshield Lens Coating	Yes	
FOV	40°	
Range of Focus	0.2 m to infinity	
Diopter Adjustment	-6 to +2	
Controls	Direct	
Automatic Brightness Control	Yes	
Bright Light Cut-off	Yes	
Automatic Shut-off System	Yes	
Infrared Illuminator	Yes	
IR Indicator	Yes (in FOV)	
Low Battery Indicator	Yes (in FOV)	
Power Supply	2 x 1.5 V AA type battery or 1 x 3 V BA-5567/U type battery	
Battery Life	60 hrs	
Environmental Rating	Waterproof	
MIL-STD-810	Complies	
Operating Temperature	-51°C to +49°C / -60 to 120F	
Storage Temperature	-51°C to +85°C / -60 to 185F	
Dimensions	162x152x76mm/6.375"x6"x3"	
Weight	680g/.68kg/1.5lb	

TUBE SPECIFICATIONS

LICH OLIVI	ITV CCT	CEN	INAACE	INTENSIFIER	TIIDE
HIGH GUAL	IIY GGI		IIVIAtat	III I FIN SIFIFR	TUBE

HIGH QUALITY GGT GEN IMAGE INTENSIFIER TUBE		
DESCRIPTION	Custom	
GENERATION	CGT	
PHOTOCATHODE TYPE	Multi - Alkali	
RESOLUTION, Ip/mm *	45-54	
SIGNAL TO NOISE RATIO*	16-22	
FIGURE OF MERIT	<1250	
MTTF - MEAN TIME BEFORE FAILURE, hours	10,000	
EXPORT	N/A for Export	
* Charifications are provided for informational purposes only. Actual values may your		

* Specifications are provided for informational purposes only. Actual values may vary

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.