




THE FUTURE
OF OPTICS


















www.atncorp.com



DAY •
NIGHT •
THERMAL •

2021



X-Sight LTV Series DAY & NIGHT DIGITAL RIFLE SCOPES		page 4
X-Sight 4K Pro Series DAY & NIGHT SMART HD RIFLE SCOPES		page 4
X-Sight 4K Buck Hunter Series DAYTIME SMART HD RIFLE SCOPES		page 4
ThOR LT Series THERMAL RIFLE SCOPES		page 5
ThOR 4 Series THERMAL SMART HD RIFLE SCOPES		page 5
OTS-XLT Series HANDHELD THERMAL MONOCULARS		page 6
BinoX 4K 4-16x DAY & NIGHT SMART HD BINOCULAR		page 7
BinoX 4T Series THERMAL SMART HD BINOCULARS		page 8
OTS 4T Series THERMAL SMART HD MONOCULARS		page 9
OTS LT Series THERMAL HD MONOCULARS		page 10
Auxiliary Ballistic Laser 1000/1500 LASER RANGEFINDERS		page 11
IR850 Supernova EXTREME RANGE INFRA-RED ILLUMINATOR		page 12
IR850 Pro LONG RANGE INFRA-RED ILLUMINATOR		page 12
Power Weapon Kit 20,000 mAh BATTERY PACK		page 12
Extended Life Battery Kit 10,000 mAh BATTERY PACK		page 12
X-TRAC TACTICAL REMOTE ACCESS CONTROL		page 12
Quick Detach Mount RETAIN ZERO WHEN SWAPPING BETWEEN PLATFORMS		page 12

SMART HD OPTICS

What are Smart HD Optics?

Smart HD Optics are nothing short of the most advanced electro-optics available.

Smart HD Optics bring the modern technology of smart phones, digital cameras and military electro-optics to the analog sporting optics market, creating a whole new revolutionary sporting optics field! ATN's Smart HD Optics now comprise the majority of our product line from day/night sights, binoculars and spotting scopes to thermal scopes, binoculars and viewers. Each and every one of these devices are powered by the ATN Obsidian Core.

Offering unprecedented features and improved image performance, the Obsidian Core has transformed ATN's product line, and has set a new standard for our industry. The Obsidian Core is a sensor-neutral micro-computer powered by an advanced ARM based processor, that hosts an array of sensors. Utilizing a Full HD (1920x1080) sensor for our day/night systems and either a 640x480 or 384x288 thermal sensor for our new HD thermal line of products. The Obsidian Core creates a uniform platform for our Smart HD devices.

Our all new Smart HD systems offer you many of the same features and functions you are now familiar with from our other SMART HD product lines. Utilizing the same intuitive UI (User Interface) and mobile Obsidian app platform. Once familiar with one of our Smart HD devices, using any other device is simple. All our smart systems offer high definition onboard video recording and photo capture; making sharing your experiences a breeze. Plenty of processing power, also means that these systems offer new and improved image quality and performance. And since now all our new scopes are powered by the Obsidian Core, we can pass on the savings and make our products more affordable.

ULTRA HD OPTICS

ATN is proud to deliver the next generation in innovation. Ultra HD Optics offers you image quality never before seen in digital optics. ATN's new 4K "True Color" Sensor is capable of capturing crisp clear images at the furthest ranges with increased color resolution and smooth gradations from darkness to light. All 4th Gen Optics have been redesigned to meet strict 600 lp/mm specifications to match our 4K sensor performance. The new Dual Core Processor that drives our core allows for faster response, higher FPS rate, better streaming, and the use of a multitude of new image processing techniques.

The next several pages will help familiarize you with just some of the amazing features the new Smart HD Optics have to offer.

THE FUTURE OF OPTICS IS HERE!

* For more details see www.atncorp.com



AMERICAN TECHNOLOGIES NETWORK CORP. HQ
1341 San Mateo Ave., S. San Francisco, CA 94080
TOLL FREE 800-910-2862 PHONE 650-989-5100
info@atncorp.com www.atncorp.com

AMERICAN TECHNOLOGIES NETWORK CORP.
DISTRIBUTION AND SALES
12250 NW 102nd Place, Doral, FL 33172
PHONE 305-900-6841

The products in this catalog are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.



X-SIGHT LTV SERIES

DAY & NIGHT DIGITAL RIFLE SCOPES



- DAY/NIGHT MODE
- RECORD HD VIDEO
- MULTIPLE RETICLES
- 3D GYROSCOPE
- LONG LASTING INTERNAL BATTERY

SPECIFICATIONS

	X-Sight LTV 3-9x	X-Sight LTV 5-15x
Item #	DGWSXS309LTV	DGWSXS515LTV
Lens	30 mm	50 mm
Magnification	3-9x	5-15x
Sensor	ATN QHD+ M584 Sensor	
Sensor Resolution	2688 x1944 @ 60 fps	
Core	ATN Obsidian LT Core	
Micro Display	1280x720 px	
Eye relief	90 mm	
3D Gyroscope	Yes	
3D Accelerometer	Yes	
Night Vision Mode	Yes	
Video Record	Yes	
Reticles	Multiple Patterns	
Video Record Resolution	1280x720	
Micro SD Card	4 Gb to 64 Gb	
USB, type C	Charging Port	
Mount	30 mm Standard Rings (included)	
IR Illuminator	Included	
Battery life (Li-ion)	≈10 hrs	
Battery type	Internal Lithium Ion Battery	
Waterproof rating / IP rating	Weather resistant	
Operating Temperature	-20°F to +120°F / -28°C to 48°C	
Dimensions (body only)	12.2"x2.2"x2.2" / 310x55x55 mm	13"x2.2"x2.2" / 330x55x55 mm
Weight	1.6 lb / 745 g	1.7 lb / 780 g
Warranty	2 years	

*Specifications subject to change without notice.

X-SIGHT 4K PRO SERIES

DAY & NIGHT SMART HD RIFLE SCOPES



5-20x



3-14x

SPECIFICATIONS

	X-Sight 4K Pro 3-14x	X-Sight 4K Pro 5-20x
Item #	DGWSXS3144KP	DGWSXS5204KP
Magnification	3-14x	5-20x
Field of view at 1000 yds	460 ft (9°)	240 ft (5°)
Sensor	ATN 4K M265 Sensor, 3864 (H) x 2218 (V)	
Core	ATN Obsidian IV Dual Core	
System Resolution	600 lp/mm	
Micro Display	1280x720 HD Display	
Eye relief	90 mm	
Video Record Resolution	1080p @ 30/60/120 fps**	
Ballistic Calculator	Yes	
WiFi (Streaming, Gallery, & Controls)	iOS & Android	
Night Vision Mode	Yes	
Reticles	Multiple Patterns & Color Options	
Micro SD card	4 to 64 GB	
USB, type C	Yes	
Mount	30 mm Standard Rings	
IR Illuminator	Included	
Battery life (Li-ion)	18+ hrs	
Battery type	Internal Lithium Ion Battery	
Waterproof rating / IP rating	Weather resistant	
Dimensions (body only)	13.8"x3"x3" / 350x76x76 mm	14.9"x3"x3" / 379x76x76 mm
Weight	2.1 lb / 0.94 kg	2.2 lb / 1.01 kg
Warranty	2 years	

*Specifications subject to change without notice.

**When choosing to use this option, the incorporation of your widgets are absent. Widgets would include reticle, time stamp, and logo that are added during video processing.

- HD VIDEO WITH 30/60/120 FPS
- BALLISTIC CALCULATOR
- RECOIL ACTIVATED VIDEO (RAV)
- SMART RANGEFINDER
- SMART MIL DOT RETICLE
- SHARE ON SOCIAL MEDIA
- ONE SHOT ZERO
- ULTRA LOW POWER CONSUMPTION
- PROFILE MANAGER

OPTIONAL ACCESSORIES



ATN X-TRAC Remote Control



AUXILIARY BALLISTIC LASER Rangefinder Series



ATN LASERBALLISTICS Rangefinder Series



ATN IR 850 Pro IR Illuminator



ATN WEAPON BATTERY PACK



ATN QUICK DETACH MOUNT

THOR LT SERIES THERMAL RIFLE SCOPES



- 📦 LIGHT WEIGHT
- 👁 ERGONOMIC DESIGN
- 🔌 USB TYPE C
- 🔄 MULTIPLE RETICLES
- ⚡ ULTRA LOW POWER CONSUMPTION

SPECIFICATIONS

Item #	ThOR LT 160		ThOR LT 320			
	TIWSTLT136X	TIWSTLT148X	TIWSTLT1319X	TIWSTLT1325X	TIWSTLT1335X	TIWSTLT1350X
Objective lens	19 mm	25 mm	19 mm	25 mm	35 mm	50 mm
Resolution	160x120 px 17 µm 60 Hz		320x240 px 12 µm 60 Hz			
Magnification	3-6x	4-8x	2-4x	3-6x	4-8x	5-10x
Field of view	8.1°x6.2°	6.2°x4.7°	11.6°x8.7°	8.8°x6.6°	6.3°x4.7°	4.4°x3.3°
Display Resolution	1280x720 px					
Eye relief	90 mm					
3D Accelerometer	Yes					
Color modes	White Hot / Black Hot					
Reticles	Multiple Patterns					
USB, type C	Charging					
Mount	30 mm Standard Rings (not included)					
Battery life (Li-ion)	10+ hrs					
IP rating	Weather resistant					
Human Detection Range	475 m	625 m	715 m	910 m	1510 m	1620 m
Human Recognition Range	240 m	315 m	305 m	455 m	680 m	710 m
Human Identification Range	160 m	210 m	200 m	290 m	400 m	415 m
Operating Temperature	-20°F to +120°F / -28°C to 48°C					
Dimensions	292x56x55 mm / 11.5" x 2.2" x 2.2"					
Weight	1.4 lb / 650 g					
Warranty	3 years					

*Specifications subject to change without notice

THOR 4 SERIES THERMAL SMART HD RIFLE SCOPES



- 🎯 BALLISTIC CALCULATOR
- 📹 RECOIL ACTIVATED VIDEO (RAV)
- 📏 SMART RANGEFINDER
- 🧭 E-COMPASS
- 📏 SMART MIL DOT RETICLE
- 📱 SHARE ON SOCIAL MEDIA
- 🎯 ONE SHOT ZERO
- ⚡ ULTRA LOW POWER CONSUMPTION
- 📁 PROFILE MANAGER

SPECIFICATIONS

	ThOR 4 384 1.25-5x	ThOR 4 384 2-8x	ThOR 4 384 4.5-18x	ThOR 4 384 7-28x	ThOR 4 640 1-8x	ThOR 4 640 1.5-15x	ThOR 4 640 2.5-20x	ThOR 4 640 4-40x
Item #	TIWST4381A	TIWST4382A	TIWST4384A	TIWST4387A	TIWST4641A	TIWST4642A	TIWST4643A	TIWST4644A
Sensor	Gen 4 384x288				Gen 4 640x480			
Magnification	1.25-5x	2-8x	4.5-18x	7-28x	1-10x	1.5-15x	2.5-25x	4-40x
Field of view	16°x12.5°	12°x9.5°	6°x4.7°	5°x3.8°	32°x25°	24°x19°	12.5°x9.7°	8.3°x6.2°
Core	ATN Obsidian IV Dual Core T							
Micro Display	1280x720 HD Display							
Eye relief	90 mm							
Video Record Resolution	1280x960 @ 30/60 fps							
WiFi (Streaming, Gallery, & Controls)	iOS & Android							
RAV (Recoil Activated Video)	Yes							
Reticles	Multiple Patterns & Color Options							
Micro SD card	From 4 to 64 GB							
USB, type C	Yes							
Mount	30 mm Standard Rings (included)							
Internal Lithium Ion Battery	18+ hrs				16+ hrs			
Waterproof rating / IP rating	Weather resistant							
Dimensions	13.1"×3"×3" 332×76×76 mm	13.5"×3"×3" 343×76×76 mm	13.8"×3"×3" 351×76×76 mm	14.8"×3"×3" 375×76×76 mm	13.1"×3"×3" 332×76×76 mm	13.5"×3"×3" 343×76×76 mm	13.8"×3"×3" 351×76×76 mm	14.8"×3"×3" 375×76×76 mm
Weight	1.93 lb / 0.88 kg	2.03 lb / 0.92 kg	2.2 lb / 1.0 kg	2.35 lb / 1.06 kg	1.93 lb / 0.88 kg	2.03 lb / 0.92 kg	2.2 lb / 1.0 kg	2.35 lb / 1.06 kg
Warranty	3 years							
Human Detection Range	750 m	960 m	1800 m	3000 m	830 m	1050 m	1950 m	3300 m
Human Recognition Range	335 m	480 m	720 m	1320 m	350 m	530 m	800 m	1450 m
Human Identification Range	205 m	300 m	430 m	720 m	225 m	330 m	475 m	800 m

*Specifications subject to change without notice

OTS-XLT SERIES HANDHELD THERMAL MONOCULARS



19 mm

25 mm


- ERGONOMIC DESIGN
- RANGEFINDER
- RECORD VIDEO
- COLOR MODES
- USB TYPE C

DESCRIPTION

The handheld thermal monocular is a handheld device for observation, highest temperature target tracking, distance measurement. The high-sensitivity built-in thermal detector provides you with clear view even in total darkness. The device is mainly applied to outdoor scenarios such as patrolling, law enforcement, search and rescue, drug enforcement, anti-smuggling, hiking, travel, and hunting, etc.

SMART RANGEFINDER

The device can detect the distance between the target and the observation position.



SPECIFICATIONS

	OTS-XLT 160 2-8x	OTS-XLT 160 2.5-10x
Lens	19 mm	25 mm
Sensor	160x120 px / 17 μm 50 Hz	
Magnification	2 – 8×	2.5 – 10×
Field of view, degrees	8.2×6.2	6.5×4.9
Core	ATN Obsidian Core LT	
Micro Display	720×540 px	
IP rating	IP67	
Charging	USB, type C	
Video Record Resolution	720×576 px	
Internal Storage	8 Gb	
Color modes	White Hot / Black Hot / Red Hot / Color	
Battery life (Li-ion)	≈10 hr	
Operating Temperature	-4°F to +131°F / -20°C to 55°C	
Dimensions	6.85" × 2.63" × 2.08" / 174 × 67 × 53 mm	
Weight	0.81 lb/370 g	
Human Detection Range, m	670	850
Human Recognition Range, m	335	425
Human Identification Range, m	170	210
Warranty	2 years	

*Specifications subject to change without notice

www.atncorp.com e-mail: sales@atncorp.com, info@atncorp.com

BLACK HOT / WHITE HOT COLOR MODE



*scope view


BINOX 4K 4-16X

DAY & NIGHT SMART HD BINOCULAR W/ BUILT-IN LASER RANGEFINDER



IMAGE QUALITY

4K Ultra HD technology, combined with our cutting edge Dual Core Processor, gives you unsurpassed image quality with richer and more vivid color tones. Providing the end user with a visual experience like no other.



* binocular view

RECORD HD VIDEO



Make capturing your experiences in stunning 1080p a regular part of your adventures. No more missed opportunities of that once in a lifetime moment. ATN expands the boundaries of Full HD video recording with rich colors and sharp details. Just insert an SD card to shoot your hunting episodes without any additional USB cables. Bring your successes back home and share with friends, family and on social media. Never miss a chance to catch your accomplishments on video.

LASER RANGEFINDER

The new 4K Sensor was incorporated for better visibility and crisper images, but we didn't stop there. We integrated a Laser Rangefinder, so you now have the ultimate binocular package that has everything you want. Not only do you have the ability to see both day and night at your fingertips, but you now have the ability to range your target with absolute accuracy for dope hold over or know how far you need to trek to your next waypoint.



DUAL STREAM VIDEO

By incorporating a Dual Core Processor, we are now able to provide a much more enhanced experience. Now, you can Live Stream via WiFi to a mobile device, and record in your binoculars at the same time, without lag or loss of performance.



SPECIFICATIONS


	BinoX 4K 4-16x
Item #	DGBNBN4KLRF
Sensor	ATN 4K M265 Sensor 3864 (H) x 2218 (V)
Magnification	4-16x
Field of view	220 ft
Objective lens	40 mm
Display Resolution	1280x720x2
Interpupillary adjustment range	60-70 mm
Eye relief	10-30 mm
Focus Range	10 ft to infinity
IR illuminator	Yes
Laser Rangefinder	Yes
Video Record Resolution	1080p @ 30/60/120fps**
Precision to	± 1 y/m
Range	5-1000 y/m
IP rating	Weather Resistant
Charging	USB, type C
WiFi (Streaming, Gallery, & Controls)	iOS & Android
Micro SD Card	4 to 64 GB
Battery life (Li-ion)	18+ hrs
Dimensions	9.4" x 5" x 2.6" / 240 x 128 x 67 mm
Weight	2.5 lb / 1.12 kg
Warranty	2 years

*Specifications subject to change without notice.

**When choosing to use this option, the incorporation of your widgets are absent. Widgets would include reticle, time stamp, and logo that are added during video processing.

BINOX 4T SERIES

THERMAL SMART HD BINOCULARS W/ BUILT-IN LASER RANGEFINDER




LASER RANGEFINDER

We integrated a Laser Rangefinder, so you now have the ultimate binocular package that has everything you want. Not only do you have the ability to see both day and night at your fingertips, but you now have the ability to range your target with absolute accuracy for dope hold over or know how far you need to trek to your next waypoint.



IMAGE QUALITY

By combining Cutting-Edge thermal technology with our Dual Core Processor, we are able to deliver unsurpassed image quality. Giving the end user a visual experience like no other.



* binocular view

DUAL STREAM VIDEO

By incorporating a Dual Core Processor, we are now able to provide a much more enhanced experience. Now, you can Live Stream via WiFi to a mobile device, and record in your scope at the same time, without lag or loss of performance.



SPECIFICATIONS

	BinoX 4T 1.25-5x	BinoX 4T 2-8x	BinoX 4T 4.5-18x	BinoX 4T 1-10x	BinoX 4T 1.5-15x	BinoX 4T 2.5-25x
Item #	TIBNBX4381L	TIBNBX4382L	TIBNBX4384L	TIBNBX4641L	TIBNBX4642L	TIBNBX4643L
Sensor	384x288			640x480		
Magnification	1.25-5x	2-8x	4.5-18x	1-10x	1.5-15x	2.5-25x
Field of view	16°x12.5°	12°x9.5°	6x4.7°	32°x25°	24°x19°	12.5°x9.7°
Display Resolution	1280x720x2 px					
Interpupillary adjustment range	60-70 mm					
Eye relief	10-30 mm					
Focus Range	10 ft to infinity					
Laser Rangefinder	Yes					
Precision to	± 1 y/m					
Range	5-1000 y/m					
Video Record Resolution	1280x960p @ 30/60fps					
IP rating	Weather Resistant					
Charging	USB, type C					
WiFi (Streaming, Gallery, & Controls)	iOS & Android					
Micro SD Card	4 to 64 GB					
Battery life (Li-ion)	15+ hrs					
Human Detection Range	750 m	960 m	1800 m	830 m	1050 m	1950 m
Human Recognition Range	335 m	480 m	720 m	350 m	530 m	800 m
Human Identification Range	205 m	300 m	430 m	225 m	330 m	475 m
Dimensions	9.4" x 5" x 2.6" / 240 x 128 x 67 mm					
Weight	2.5 lb / 1.12 kg					
Warranty	3 years					

* Specifications subject to change without notice

www.atncorp.com e-mail: sales@atncorp.com, info@atncorp.com

OTS 4T SERIES THERMAL SMART HD MONOCULARS



CUTTING EDGE DUAL CORE THERMAL SENSOR

We've combined the next generation thermal sensor with our dual core processor giving you the best thermal monocular ever! Join the thermal evolution!

FEATURES

IMAGE QUALITY

By combining Cutting-Edge thermal technology with our Dual Core Processor, we are able to deliver unsurpassed image quality. Giving the end user a visual experience like no other.

DUAL STREAM VIDEO

By incorporating a Dual Core Processor, we are now able to provide a much more enhanced experience. Now, you can Live Stream via WiFi to a mobile device, and record in your scope at the same time. Without lag or loss of performance.

RECORD VIDEO


This feature gives you the opportunity to capture your experiences on video. Using an SD card allows you to record your adventures without any additional USB cables. Never missing a chance to catch your moment on video.

E-COMPASS

DUAL CORE PROCESSOR

SHARE ON SOCIAL MEDIA

ULTRA LOW POWER CONSUMPTION



OPTIONAL ACCESSORIES



ABL 1000 LASER RANGEFINDER



ABL 1500 LASER RANGEFINDER

SPECIFICATIONS

	OTS 4T 384 1.25 - 5x	OTS 4T 384 2 - 8x	OTS 4T 384 4.5 - 18x	OTS 4T 384 7 - 28x	OTS 4T 640 1 - 10x	OTS 4T 640 1.5 - 15x	OTS 4T 640 2.5 - 20x	OTS 4T 640 4 - 40x
# Item	TIMNO4381A	TIMNO4382A	TIMNO4384A	TIMNO4387A	TIMNO4641A	TIMNO4642A	TIMNO4643A	TIMNO4644A
Sensor	Gen 4 - 384x288				Gen 4 - 640x480			
Magnification	1.25 - 5x	2 – 8x	4.5 – 18x	7 – 28x	1 – 10x	1.5 – 15x	2.5 – 25x	4 – 40x
Field of view, degrees	16x12.5	12x9.5	6x4.7	5x3.8	32x25	24x19	12.5x9.7	8.3x6.2
Core	ATN Obsidian IV Dual Core T							
Micro Display	1280x720 HD Display							
Eye relief	25 mm							
Video Record Resolution	1280x960 @ 30/60 fps							
WiFi (Streaming, Gallery, & Controls)	iOS & Android							
Bluetooth	Yes							
3D Gyroscope	Yes							
3D Accelerometer	Yes							
E-Barometer	Yes							
Smart Range Finder	Yes							
Electronic Compass	Yes							
Smooth Zoom	Yes							
Microphone	Yes							
Micro SD card	From 4 to 64 GB							
Micro USB, type C	Yes							
Internal Lithium Ion Battery	18+ hrs				16+ hrs			
Waterproof rating / IP rating	Weather resistant							
Dimensions	8.7"x3.1"x3" 220x80x75 mm	8.7"x3.1"x3" 220x80x75 mm	9.3"x3.1"x3" 235x80x75 mm	10.2"x3.1"x3" 260x80x75 mm	8.7"x3.1"x3" 220x80x75 mm	8.7"x3.1"x3" 220x80x75 mm	9.3"x3.1"x3" 235x80x75 mm	10.2"x3.1"x3" 260x80x75 mm
Weight	850 g / 1.87 lb	850 g / 1.87 lb	875 g / 1.93 lb	900 g / 1.98 lb	850 g / 1.87 lb	850 g / 1.87 lb	875 g / 1.93 lb	900 g / 1.98 lb
Warranty	3 years							
Human Detection Range	750	960	1800	3000	830	1050	1950	3300
Human Recognition Range	335	480	720	1320	350	530	800	1450
Human Identification Range	205	300	430	720	225	330	475	800

*Specifications subject to change without notice

www.atncorp.com e-mail: sales@atncorp.com, info@atncorp.com

OTS LT SERIES THERMAL MONOCULARS



19 mm

25 mm

35 mm

SPECIFICATIONS

	OTS LT 160		OTS LT 320			
Item #	TIMNOLT136X	TIMNOLT148X	TIMNOLT319X	TIMNOLT325X	TIMNOLT335X	TIMNOLT350X
Lens	19 mm	25 mm	19 mm	25 mm	35 mm	50 mm
Resolution	160x120 px / 17 μm 60 Hz		320x240 px / 12 μm 60 Hz			
Magnification	3-6x	4-8x	2-4x	3-6x	4-8x	6-12x
Field of View	8.1°x6.2°	6.2°x4.7°	11.4°x8.6°	8.8°x6.6°	6.3°x4.7°	4.5°x3°
Display Resolution	1280x960 px					
Eye relief	25 mm					
Color modes	White Hot / Black Hot					
Internal Lithium Ion Battery	10+hr		9+hr			
USB, type C	Charging					
IP rating	Weather resistant					
Human Detection Range	475 m	625 m	535 m	910 m	1510 m	1700 m
Human Recognition Range	240 m	315 m	380 m	455 m	680 m	700 m
Human Identification Range	160 m	210 m	230 m	290 m	340 m	400 m
Operating Temperature	-20°F to +120°F / -28°C to 48°C					
Dimensions	7.7" x 3" x 2.6" / 196x76x66 mm					
Weight	1.2 lb / 560 g					
Warranty	3 Years					



*scope view

*Specifications subject to change without notice

- ERGONOMIC DESIGN
- ATN OBSIDIAN LT CORE
- LONG LASTING INTERNAL BATTERY
- USB TYPE C

IMAGE QUALITY



Using our new Obsidian LT Core and Cutting-Edge sensors for sharp crisp images and extended range.




Comfortable
25 mm eye relief

Ergonomic
and Simple to use

320x240

AUXILIARY BALLISTIC LASER 1000/1500 LASER RANGEFINDERS



*scope view



SENDING DISTANCE
TO THE BALLISTICS CALCULATOR

TURN YOUR ATN SMART SIGHT INTO A PRECISE HUNTING MACHINE!

Simple and Quick to attach, the ABL Smart Rangefinder takes just minutes to install. Once active, your ATN Smart Scope's internal Ballistic Calculator will make Instantaneous POI adjustments to your reticle.

MAKE EVERY SHOT COUNT!

COMPATIBLE WITH



SPECIFICATIONS

	ABL 1000 FMG	ABL 1500 FMG
ITEM #	ACMUABL1000	ACMUABL1500
Precision to	± 1 y/m	
Range	5-1000 y/m	5-1500 y/m
Bluetooth	4.1	
Environmental rating	Waterproof	
Pairs with smart HD	Obsidian II or higher	
Smart HD optics compatibility	X-Sight 4K Series, ThOR 4 Series	
Battery life	6 months or 5,000 measurements	
Battery type	1 x CR2 type, 3 V	
Dimensions	4.37" x 3.43" x 2.8" / 111 x 87 x 71 mm	
Weight	0.8 lb / 360 g	
Warranty	2 years	

*Specifications subject to change without notice

IR850 SUPERNOVA

EXTREME RANGE INFRA-RED ILLUMINATOR



SPECIFICATIONS

Item #	ACMUIR85SN
LED Module	High power emitter with IR850 Xtreme driver
Lens	Aspherical glass
Material	Constructed using aircraft grade aluminium
Surface	Type III hard anodized with highly durable finish
Waterproof	IPX-8
Battery type	18650 rechargeable, 3.7 V Lithium ion
Dimensions	6.3"×3.3"×2.1" / 160×84×54 mm
Weight	0.83 lb / 380 g

*ATN reserves the right to change the above specifications at any time without notice.

IR850 PRO

LONG RANGE INFRA-RED ILLUMINATOR



SPECIFICATIONS

Item #	ACMUIR85PR
LED Module	High power emitter with IR850 Pro driver
Lens	Aspherical glass
Material	Constructed using aircraft grade aluminium
Surface	Type III hard anodized with highly durable finish
Waterproof	IPX-8
Battery type	18650 rechargeable, 3.7 V Lithium ion
Dimensions	6.3"×3.3"×2.1" / 160×84×54 mm
Weight	0.83 lb / 380 g

*ATN reserves the right to change the above specifications at any time without notice.

POWER WEAPON KIT

20,000 mAh BATTERY PACK



DESCRIPTION

The ATN Extended Power Kit gives you plenty of juice whenever and wherever you need it. Up to 20 hrs of continuous use. Easy to recharge and can power other devices. Designed to be used with the ATN line of Smart HD Optics: X-Sight 4K BH, X-Sight 4K Pro and ThOR 4.

EXTENDED LIFE BATTERY KIT

10,000 mAh BATTERY PACK



DESCRIPTION

Don't let yourself be stuck without a functioning unit, because you didn't bring extra batteries to power your device. ATN Extended Life Battery kit can support your binoculars or monoculars for up to 15 hrs. You can use your devices longer and save money and the environment in the process. Enjoy your activities all day long — whether scouting, camping, bird watching, or surveillance. You can even power your none ATN devices, which are compatible with a micro USB. Designed to be used with the ATN line of Smart HD Optics: BinoX 4K and BinoX 4T.

X-TRAC

TACTICAL REMOTE ACCESS CONTROL



SPECIFICATIONS

Item #	ACMURCNTRL1
Bluetooth	4.0
Environmental rating	Water resistant
Battery type	CR2450
Controls	6 Tactile buttons and a Roller
Dimensions	3.2"×2"×0.8" / 80×50×21 mm
Weight	1.76 oz / 50 g

*ATN reserves the right to change the above specifications at any time without notice.

QUICK DETACH MOUNT

RETAIN ZERO WHEN SWAPPING BETWEEN PLATFORMS



DESCRIPTION

The ATN Quick Detach Mount is a great addition for your new X-Sight 4K or ThOR 4. Take advantage of the profile manager of your scope, move it from platform to platform and still retain zero.



THE FUTURE OF OPTICS 2021

www.atncorp.com



DAY.
NIGHT.
THERMAL.

